

CYCLE 2022-01

Sorting order:

A – first 'quotas', then 'suspensions'

B – **new** requests, **amending** requests.

In addition, at the end of this document (p.41 onwards) you will find the existing battery related suspensions, which will be reviewed in the upcoming cycle.

>>>The duty suspension and quota requests on the following list are currently under discussion. The data available on this list may not represent the final state of the discussions within the relevant Commission Working group.

Please note that it cannot be guaranteed that the information available exactly reproduces an officially adopted text. Only European Union legislation published in the Official Journal of the European Union is deemed authentic<<<

CN code	TARIC	Reference Mail	Working Number	Description	Quotas	New or amendment request	Measure status	Partner Position Country	Partner Position	Public Comments
ex 7607 11 19	61	4955605/2020	0750	Aluminium foil in rolls of a width exceeding 650 mm with: - an aluminium purity by weight of 99 % or more but not more than 99,95 %, - a thickness of 10 µm or more, but not more than 15 µm, - a surface oxide layer, for use [as cathode] in the manufacturing of lithium-ion electric rechargeable batteries (1)	Q/ 1500tonnes, 01.01-30.06	Amendment	UNDER EXAMINATION	DE EU TR	Applicant Opposed Opposed	Round 2022-01 - amendment Round 01.07.2021 for use in the manufacturing of lithium-ion electric rechargeable batteries

CN code	TARIC	Reference Mail	Working Number	Description	Suspensions	New or amendment request	Measure status	Partner Position Country	Partner Position	Public Comments
7606 12 99		1957455/2021	1074	AMS (Aerospace Materials Specification) and/or BAMS(Bombardier Aerospace Materials Specification) spesified 7040 or 7050 series,	S	New	UNDER EXAMINATION	TR	Applicant	Round 2022-1 used in the manufacture of products of aerospace industry

				NADCAP(National Aerospace and Defense Contractors Accreditation Program) and AS9100(Aerospace Basic Quality System Standard) certified, aluminum alloy plates with a <ul style="list-style-type: none"> - width of 1000mm or more but not more than 2000mm, - thickness of 1000mm or more but not more than 2000mm used in the manufacture of products of aerospace industry (1)						
ex 7601 20 20	10	1073/2007	3210	AT+ SL(12.03.2021) new proposal: Slabs and billets of aluminium alloy containing by weight 0,8 % or more of lithium --- Current product description: Slabs and billets of aluminium alloy containing lithium	S	Amendment	UNDER EXAMINATION	FR	Applicant	Round 2022-01 - request for amendment.
ex 8104 19 00	10	1710324/2020	3101	Unwrought magnesium containing 90 % or more but not more than 99,7 % by weight of magnesium	S	Amendment	UNDER EXAMINATION	DE AT DE	Applicant Co-applicant Opposed	Round 2022-01- Objection Production of Steering wheel - frame skeleton from magnesium die casting alloys.
ex 7607 11 90 ex 7607 11 90	65 67	862/2006	0912	Plain aluminium foil with the following parameters: <ul style="list-style-type: none"> - an aluminium content of 99,98 % or more, - a thickness of 0,070 mm or more but not more than 0,125 mm, - with a cubic texture, of a kind used for high voltage etching	S	Amendment	UNDER EXAMINATION	FR EU	Applicant Opposed	Round 2022-01 - review of the suspension.

ex 7607 20 90	10	4697798/2018	0913	Aluminium foil, in rolls: - coated on one side with polypropylene or polypropylene and acid-modified polypropylene and on the other with polyamide and polyethylene terephthalate, with adhesive layers between them, - with a width of 200 mm or more, but not more than 400 mm, - with a thickness of 0,138 mm or more, but not more than 0,168 mm, for use in the manufacture of lithium-ion battery cell covers (1)	S	Amendment	UNDER EXAMINATION	PL EU	Applicant Opposed	Round 2022-01 - review of the suspension. for use in the manufacture of lithium-ion battery cell covers
ex 7616 99 90	35	1895600/2020	0914	Aluminum plate with: - a length of 36 mm or more but not more than 49 mm, - a width of 29,8 mm or more but not more than 45,2 mm, - a thickness of 0,18 mm or more but not more than 0,66 mm, equipped with a polypropylene tape with: - a length of 6,5 mm or more but not more than 16,5 mm, - a width of 39 mm or more but not more than 56 mm, - characteristic allowing to create solid joint with Pouch external layer by melting process assuring leak and pressure proof sealing of Cell, - resistance to influence of electrolyte, for use in the manufacture of lithium-ion battery cells for motor vehicle batteries (1)	S	Amendment	UNDER EXAMINATION	PL EU	Applicant Opposed	Round 2022-01 - review of the suspension. aluminium plate (known as Lid) used as the positive output for manufacturing Li ion battery cells used in electric cars

(1) Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013 of the European Parliament and of the Council of 9 October 2013 laying down the Union Customs Code (OJ L 269, 10.10.2013, p. 1)